



## DIESEL ENGINE



EV2400



RV165

Model	RV70N	RV125-2N	RV125-2NB	RV165-2N	RV325N	EV2400N	EV2400NB	EV2600N
Engine Category	4-cycle, 1-cylinder, horizontal							
Bore*Stroke (mm)	80*75	94*90		105*97	120*125	116*105		118*108
Displacement (ml)	376	624		839	1413	1109		1181
Cont. Output (hp/RPM)	6/2200	10.5/2200		14/2200	26/2200	17/2200		20/2200
Max. Output (hp/RPM)	7/2400	12.5/2400		16.5/2400	30/2400	22/2400		25/2400
Max. Torque (kgf/RPM)	2.26/1800	4.04/1800		4.9/1800	9.7/1400	8.3/1400		8.92/1400
Compression Ratio	24	18		20	18.5		17	
Fuel	Diesel							
Fuel Tank Capacity (L)	7.5	10.5		11	17		16	
Specific Fuel Consumption (g/hp/hr)	203	185		175	190		180-190	
Combustion System	Direct Injection							
Starting System	Handle Start		Electric Start		Handle Start		Electric Start	Handle Start
Cooling System	Radiator							
Cooling Water Capacity (L)	8.5	2.1		2.6		4.7		
Packing Dimension (cm)	61.9*32.3*45.2	74.7*37*47.2	74.7*37*48.1	75.9*38.8*49.6	102.8*49.2*76.2		94.3*45.3*66.7	



RV325



RV125



RV70